


Date	SYM	REVISION RECORD	AUTH	DR.	CK.
01/10/14	A	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	
09/04/15	B	ADDED NOTCH	T.B.	B.S.	
04/27/18	C	Updated Positive contact design	T.B.	B.S.	

**SPECIFICATIONS:**

- \* Holder material- LCP Vectra, Color white, UL File No. E174096
- \* Contacts : Phosphor Bronze C5191, Gold Flash, 1u - 3u thickness
- \* Temperature range: -40°C to +280°C
- \* Vibration Test: 10-50-10 Hz swept in 60 seconds  
X,Y,Z direction: 1 hour each direction
- \* Result: No dislodgement of the cell or damage  
No discontinuity over 10 micro-seconds
- \* Shock Test: Half sine wave acceleration 150G. 6 m/s  
3 shock pulses each direction per axis, total of 18 pulses
- \* Result: No evidence of physical damage
- \* Drop Test: 1meter - No dislodgement of cell
- \* ROHS 2 Compliant

Tolerance (Inches)	 <b>Memory Protection Devices, Inc</b> 200 Broad Hollow Road, Farmingdale, New York 11735		
Decimal ±.5 (.020)		Scale	Drawn By B.S.
		Approved By T.B.	
Fractional ± .8 (.030)	Title CR2032 BATTERY HOLDER WITH SOLDER LUG		
Angular ± 3°	Date 04/27/18	Drawing Number BHSD-2032-L	